

The YAK logo is rendered in a bold, white, italicized sans-serif font. The letters 'Y' and 'A' are connected, and the 'K' is distinct. A registered trademark symbol (®) is located at the bottom right of the 'K'.

YAK



APPLICAZIONI SPECIALI ***SPECIAL APPLICATIONS***

















Gamma di sollevatori con caratteristiche tecniche particolari, apprezzate nei settori agricoltura, movimento terra, edilizia, portuale e militare.

Special purpose jacks range, aimed at different fields such as the agricultural, earth-moving, building, port and military sectors.



SOLLEVATORE OLEOPNEUMATICO AIR HYDRAULIC JACK



| | Mod. | |
|---|---------|-----------|
| | YAK 135 | YAK 330/N |
|  | • | • |
|  | | • |
|  | | • |
|  | | • |
|  | | • |
|  | | • |
|  | | • |
|  | | • |
|  | | • |
|  | • | • |
|  | • | • |
|  | • | • |
|  | • | • |
|  | • | • |
|  | • | • |
|  | • | • |

Sollevatori Oleopneumatici per mezzi pesanti, pratici ed efficaci. Rientro automatico dei pistoni; le due valvole di discesa garantiscono una tenuta perfetta in ogni situazione e una velocità controllata sotto carico. YAK 135 Ideale per mezzi agricoli e macchine operatrici. Dotato di piastra antiribaltamento e a richiesta di ruote pneumatiche per operazioni su terreni con particolari difficoltà. YAK 330 Specifico per il sollevamento del mezzo dal telaio e per tutte le operazioni dove occorrono molta corsa e molta portata. Accessori a richiesta: ruote pneumatiche.

Air hydraulic jacks for heavy vehicles, practical and effective. The pistons move back automatically; the two descent valves guarantee perfect holding in all situations and controlled speed under load. YAK 135 Ideal for agricultural and public works vehicles. Fitted with roll-over protection plate and, on request, pneumatic wheels for working on particular difficult terrain. YAK 330 Specific for lifting the vehicle from the chassis and for all operations where maximum stroke and capacity are required. Accessories on request: pneumatic wheels.

ACCESSORI DI SERIE - STANDARD ACCESSORIES





YAK 135

YAK 330/N



YAK 135

YAK 330/N

RUOTE PNEUMATICHE PNEUMATIC WHEELS



A00496



A00502

| | YAK 135 | YAK 330/N |
|--|--------------------------------|-----------------------------------|
| Portata Capacity | 30 t <i>33 ton</i> | 80-50-25 t <i>88-55-28 ton</i> |
| Peso netto Net weight | 57 kg <i>126 lb</i> | 146 kg <i>322 lb</i> |
| Pressione di alimentazione Working air pressure | 8-10 bar <i>116-145 psi</i> | 8-10 bar <i>116-145 psi</i> |
| Consumo d'aria Air waste | 400 nl/min | 600 nl/min |
| A | 1415 mm <i>55.71 in</i> | 1430 mm <i>56.3 in</i> |
| B | 1315 mm <i>51.77 in</i> | 1320 mm <i>51.97 in</i> |
| C | 725 mm <i>28.54 in</i> | 1000 mm <i>39.37 in</i> |
| D | 275 mm <i>10.83 in</i> | 350 mm <i>13.78 in</i> |
| E | 250 mm <i>9.84 in</i> | 240 mm <i>9.45 in</i> |
| F | 350 mm <i>13.78 in</i> | 300 mm <i>11.81 in</i> |
| G | 230 mm <i>9.06 in</i> | 165 mm <i>6.5 in</i> |
| H | | 170 mm <i>6.69 in</i> |
| K | | 190 mm <i>7.48 in</i> |
| L | | 525 mm <i>20.67 in</i> |
| M | | 320 mm <i>12.60 in</i> |
| N | 30 t <i>33 ton</i> | 80 t <i>88 ton</i> |
| O | | 50 t <i>55 ton</i> |
| P | | 25 t <i>28 ton</i> |

