



SOLLEVATORI PNEUMATICI PNEUMATIC JACKS



	Mod.	
	YAK 143	YAK 143/C
	•	•
	•	•
	•	•
	•	•
	•	•
	•	•
	•	•

Sollevatori pneumatici costituiti da una membrana ad alta resistenza e da una guida telescopica interna. Sono dotati di un dispositivo d'arresto a fine corsa e di una valvola di sicurezza che li rendono assolutamente affidabili in caso di carichi eccessivi. Silenziosi, semplici e leggeri, rappresentano il prodotto ideale per gommisti e carrozzieri in funzione della possibilità di utilizzo anche sui ponti sollevatori. Disponibile inoltre la versione carrellata. **Discesa automatica. Doppia valvola di tenuta.**



Pneumatically controlled jacks consisting of a highly resistant diaphragm and internal telescopic guide. These jacks are fitted with a limit stop device as well as a safety valve making them absolutely reliable in the case of excessive loads. Silent, simple and lightweight, they are ideal for tyre repairers and bodywork shops in view of the fact they can also be used on column lifts. Also available in the trolley version.

Automatic lowering. Double valve system.

YAK 143

YAK 143/C

NEW



	YAK 143	YAK 143/C
Portata Capacity	2,0 t 2.2 ton	2,0 t 2.2 ton
Peso netto Net weight	20 kg 44 lb	23 kg 51 lb
Pressione di alimentazione Working air pressure	8 bar 116 psi	8 bar 116 psi
A	-	1109 mm 43.66 in
B	462 mm 18.2 in	462 mm 18.2 in
C	260 mm 10.2 in	260 mm 10.2 in
D	140-500 mm 5.5-19.7 in	140-500 mm 5.5-19.7 in