

SOLLEVATORE OLEOPNEUMATICO

AIR HYDRAULIC JACK



	YAK 415/N	YAK 415/R	YAK 418/N
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•
	•	•	•

Sollevatore Oleopneumatico per mezzi pesanti, pratico ed efficace. Rientro automatico dei pistoni; le due valvole di discesa garantiscono una tenuta perfetta in ogni situazione e una velocità controllata sotto carico. Una gamma completa di sollevatori per tutte le esigenze di corsa e portata. Ideale per officine, gommisti e carrozzerie.

Air hydraulic jack for heavy vehicles, practical and effective. The pistons move back automatically; the two descent valves guarantee perfect holding in all situations and controlled speed under load. A complete range of jacks for all stroke and capacity requirements. Ideal for workshops, tyre repairers and bodywork shops.

ACCESSORI DI SERIE - STANDARD ACCESSORIES





YAK 415/N

YAK 415/R

YAK 418/N



	YAK 415/N	YAK 415/R	YAK 418/N
Portata Capacity	70-43-23-13 t <i>77-47-25-14 ton</i>	70-43-23-13 t <i>77-47-25-14 ton</i>	80-50-25-15 t <i>88-55-28-17 ton</i>
Peso netto Net weight	74 kg <i>163 lb</i>	74 kg <i>163 lb</i>	77 kg <i>170 lb</i>
Pressione di alimentazione Working air pressure	8-10 bar <i>116-145 psi</i>	8-10 bar <i>116-145 psi</i>	8-10 bar <i>116-145 psi</i>
Consumo d'aria Air waste	600 nl/min	600 nl/min	600 nl/min
A	1430 mm <i>56.30 in</i>	1430 mm <i>56.30 in</i>	1430 mm <i>56.30 in</i>
B	1320 mm <i>51.97 in</i>	1320 mm <i>51.97 in</i>	1320 mm <i>51.97 in</i>
C	1000 mm <i>39.37 in</i>	1000 mm <i>39.37 in</i>	1000 mm <i>39.37 in</i>
D	320 mm <i>12.6 in</i>	320 mm <i>12.6 in</i>	320 mm <i>12.6 in</i>
E	150 mm <i>5.91 in</i>	150 mm <i>5.91 in</i>	180 mm <i>7.09 in</i>
F	250 mm <i>9.84 in</i>	250 mm <i>9.84 in</i>	300 mm <i>11.81 in</i>
G	60 mm <i>2.36 in</i>	60 mm <i>2.36 in</i>	65 mm <i>2.56 in</i>
H	68 mm <i>2.68 in</i>	68 mm <i>2.68 in</i>	72 mm <i>2.83 in</i>
L	56 mm <i>2.20 in</i>	56 mm <i>2.20 in</i>	72 mm <i>2.83 in</i>
M	66 mm <i>2.60 in</i>	66 mm <i>2.60 in</i>	91 mm <i>3.58 in</i>
N	350 mm <i>13.78 in</i>	350 mm <i>13.78 in</i>	350 mm <i>13.78 in</i>
O	240 mm <i>21.65 in</i>	240 mm <i>21.65 in</i>	240 mm <i>21.65 in</i>
P	70 t <i>77 ton</i>	70 t <i>77 ton</i>	80 t <i>88 ton</i>
Q	43 t <i>47 ton</i>	43 t <i>47 ton</i>	50 t <i>55 ton</i>
R	23 t <i>25 ton</i>	23 t <i>25 ton</i>	25 t <i>28 ton</i>
S	13 t <i>14 ton</i>	13 t <i>14 ton</i>	15 t <i>17 ton</i>
T	230 mm <i>9.06 in</i>	179 mm <i>7.05 in</i>	230 mm <i>9.06 in</i>
U	170 mm <i>6.69 in</i>	150 mm <i>5.91 in</i>	170 mm <i>6.69 in</i>

